



Myers Cloud series 4-channel IP surveillance kit consisting of an NVR and four 8MP bullet cameras. The NVR supports up to 16 cameras with recording at 16 channels at 8MP resolution at 25fps, utilizing H.265+ and H.265 video compression. Features 4 integrated 10/100 PoE ports and supports a single internal HDD up to 14TB. The included bullet cameras are equipped with 1/2.7" CMOS sensors providing 3840x2160 main stream at 10fps, 2.8mm fixed lens with 88° horizontal field of view, and dual IR/white LED illumination up to 25m. The NVR provides smart analytics including human detection, line crossing, intrusion detection, and face detection. Cameras feature IP67-rated metal housing.

Product details	
Model	4CH IP KIT
Version	8MP 4xBullet FADA
SKU	5778
Series	Cloud series

NVR	
Encoder	
Maximum cameras	16 pcs
Recording modes (IP)	16x8MP@25 fps
Video codec	H.265+, H.265
Graphical user interface	
Display resolution	2560x1440, 1920x1080, 1440x900, 1280x1024, 1280x768
Video splitter modes	1, 4, 9, 16, 2, 6
Languages	English, Russian, Arabic, French, Polish, Romanian, Hungarian, Italian, Czech
Storage	
Internal HDD	1 x 14 TB



HDD storage (important note)	For reliable 24/7 operation, it is strongly recommended to use HDDs specifically designed for video surveillance systems. Hard disk drive is not included in the package.
Network	
Network interfaces	RJ-45 (10/100Base-T)
Ethernet PoE ports	4 x 10/100 M
Network functions	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP/RTSP, NTP, SMTP, RTCP
Default IP address	DHCP
HTTP(s) port	80
Control port	34567
RTSP port	554
RTSP URL	rtsp://IP:PORT/user=LOGIN&password=PASSWORD&channel=1&stream=0.sdp
Default credentials	
Default login	admin
Default password	admin
Software	
Smart analytics	Human detection, Line crossing detection, Intrusion detection, Face detection
Smart analytics (important note)	Smart alarms can only be used with Cloud-series IP cameras
Cloud abilities	Remote access, Cloud recording, PUSH notifications
Desktop apps	Myers, Myers Setup Tool
Mobile app	Partizan
Web browsers	Google Chrome, Mozilla Firefox, Edge
Web browser usage (important note)	Web browser access requires Partizan ActiveX installation for device setup and live view. Available at www.apps.partizan.global
External interfaces	
Video output	VGA, HDMI
Audio inputs	1



Audio outputs	1
USB ports	2 x USB 2.0
Mechanical specifications	
Form factor	Desktop
Front panel material	Plastic
Housing material	Metal
Dimension	255 x 215 x 43 mm
Weight	750 g
Power	
DC power source	52 V
DC consumption	2300 mA
DC power supply	Included
Operating conditions	
Humidity range	20-95% RH (non-condensing)
Operating temperature	-40 - 60 °C
Storage temperature	-40 - 60 °C
Common	
Package contents	Optical mouse, Power adapter, 4 x Ethernet cable
Warranty	3 years

IP Camera	
Encoder	
Main stream	3840x2160@10 fps
Sub stream	800x448@25 fps
Video codec	H.264, H.265
Image sensor	
Sensor	1/2.7" CMOS
Pixel size	2.8x2.8 µm



Day/Night mode	Auto, Color, Black&White
Sensitivity	0.01 Lux
Dynamic range WDR	72 dB
S/N ratio	≤48 m
Exposure modes	Auto, Manual
Exposure range	1/25 - 1/10000 s
Video functions	AES, AES, AGC, BLC, OSD, Privacy mask, AWB, ABF
Lens	
Lens type	Spherical
Lens mount	M12
Iris	F1.6
Focal length	2.8 mm
Horizontal view	88°
Vertical view	58°
IR LED	
LED type	IR LED, White LED
Distance	≤25 m
Number of LEDs	4 pcs
Network	
Network interfaces	RJ-45 (10/100Base-T)
Network functions	DDNS, IP FILTER, Email, NTP, UPnP, RTP/RTSP, HTTP, SMTP, Cloud
Default IP address	DHCP
HTTP(s) port	80
Control port	34567
RTSP port	554
RTSP URL	rtsp://IP:PORT/user=LOGIN&password=PASSWORD&channel=1&stream=0.sdp
Default credentials	
Default login	admin



Default password	admin
Software	
Smart analytics	Human detection
Smart analytics (important note)	IP camera alarms can only be utilized with Partizan Cloud platform, Partizan mobile application, and Partizan Cloud series video recorders.
Cloud abilities	Remote access, Cloud recording, PUSH notifications
Desktop apps	Myers, Myers Setup Tool
Mobile app	Partizan
Web browsers	Google Chrome, Mozilla Firefox, Edge
Web browser languages	English, Russian, Arabic, French, Polish, Romanian, Hungarian, Italian, Czech, Ukranian
Web browser usage (important note)	Web browser access requires Partizan ActiveX installation for device setup and live view. Available at www.apps.partizan.global
Mechanical specifications	
IP rating	IP67
Dimensions	173 x 72 x 71 mm
Weight	370 g
Housing material	Metal
Mount material	Metal
Power	
DC power source	12 V
DC consumption	1000 mA
PoE	PoE Class 0
Operating conditions	
Humidity range	20-95% RH (non-condensing)
Operating temperature	-20 - 40 °C
Storage temperature	-30 - 50 °C
Common	
Package contents	Drill template, Mounting kit
Warranty	3 years

