



Myers 5MP Bullet is an IP surveillance camera equipped with a 1/2.7" CMOS sensor capturing video at 2880x1616 resolution at 25fps. Features a fixed 2.8mm spherical lens with M12 mount providing 88° horizontal and 58° field of view. Supports H.264 and H.265 video compression with dual-stream output. Includes both IR LED and white LED illumination with 30m range for day/night operation. Provides smart analytics including human detection, intrusion detection, and line crossing detection. Offers ONVIF 2.4+ protocol integration and PoE Class 0 power capability. Housed in IP67-rated metal enclosure operating from -40°C to 60°C.

Product details	
Model	5MP Bullet
SKU	5857
Encoder	
Main stream	2880x1616@25 fps
Sub stream	800x448@25 fps
Video codec	H.264, H.265
Image sensor	
Sensor	1/2.7" CMOS
Pixel size	2.8x2.8 μm
Day/Night mode	Auto, Color, Black&White
Sensitivity	0.01 Lux
Dynamic range WDR	72 dB
S/N ratio	48 dB
Exposure modes	Auto, Manual
Exposure range	1/60 - 1/10000 s
Video functions	AES, AGC, AWB, BLC, OSD, Privacy mask
Lens	
Lens type	Spherical

Lens mount	M12
Iris	F1.6
Focal length	2.8 mm
Horizontal view	88°
Vertical view	58°
IR LED	
LED type	White LED, IR LED
Distance	≤30 m
Number of LEDs	4 pcs
Network	
Network interfaces	RJ-45 (10/100Base-T)
Network functions	Cloud, DDNS, IP FILTER, Email, NTP, UPnP, RTP/RTSP, HTTPS, SMTP
Default IP address	DHCP
HTTP(s) port	80
Control port	34567
ONVIF support	ONVIF 2.4+
ONVIF port	8899
RTSP port	554
RTSP URL	rtsp://IP:PORT/user=LOGIN&password=PASSWORD&channel=1&stream=0.sdp
Default credentials	
Default login	admin
Default password	admin
Software	
Smart analytics	Human detection, Intrusion detection, Line crossing detection
Smart analytics (important note)	IP camera alarms can only be utilized with Partizan Cloud platform, Partizan mobile application, and Partizan Cloud series video recorders.
Desktop apps	Setup Tool, Myers

Mobile app	Myers
Web browsers	Google Chrome, Mozilla Firefox, Edge
Web browser languages	English, Russian, Arabic, French, Polish, Romanian, Hungarian, Italian, Czech
Web browser usage (important note)	Web browser access requires Partizan ActiveX installation for device setup and live view. Available at www.apps.partizan.global
Mechanical specifications	
IP rating	IP67
Dimensions	100 x 72 x 71 mm
Weight	400 g
Housing material	Metal
Mount material	Plastic
Power	
DC power source	12 V
DC consumption	1000 mA
PoE	PoE Class 0
Operating conditions	
Humidity range	20-95% RH (non-condensing)
Operating temperature	-40 - 60 °C
Storage temperature	-40 - 60 °C
Common	
Warranty	3 years