



Myers 8MP Bullet FADA is a network surveillance camera equipped with a 1/2.7" CMOS sensor delivering 3840×2160 resolution at 10fps on the main stream and 800×448 at 25fps on the sub stream. The camera features a 2.8mm spherical lens with M12 mount providing 88° horizontal and 58° vertical field of view, combined with IR LED and white LED illumination effective up to 25m. Supports H.264 and H.265 video compression with human detection analytics. The unit includes 72dB WDR capability and operates via 12V DC or PoE Class 0. Housed in IP67-rated metal enclosure measuring 100×72×71mm, operating from -40°C to 60°C.

Product details	
Model	8MP Bullet FADA
SKU	5859
Encoder	
Main stream	3840x2160@10 fps
Sub stream	800x448@25 fps
Video codec	H.264, H.265
Image sensor	
Sensor	1/2.7" CMOS
Pixel size	2.8x2.8 μm
Day/Night mode	Black&White, Auto, Color
Sensitivity	0.01 Lux
Dynamic range WDR	72 dB
S/N ratio	48 dB
Exposure modes	Manual, Auto
Exposure range	1/25 - 1/10000 s
Video functions	AGC, AWB, BLC, OSD, Privacy mask, AEC
Lens	
Lens type	Spherical

Lens mount	M12
Iris	F1.6
Focal length	2.8 mm
Horizontal view	88°
Vertical view	58°
IR LED	
LED type	IR LED, White LED
Distance	≤25 m
Number of LEDs	4 pcs
Network	
Network interfaces	RJ-45 (10/100Base-T)
Network functions	Cloud, DDNS, IP FILTER, Email, NTP, UPnP, RTP/RTSP, HTTPS, SMTP
Default IP address	DHCP
HTTP(s) port	80
Control port	34567
ONVIF support	ONVIF 2.4+
ONVIF port	8899
RTSP port	554
RTSP URL	rtsp://IP:PORT/user=LOGIN&password=PASSWORD&channel=1&stream=0.sdp
Default credentials	
Default login	admin
Default password	admin
Software	
Smart analytics	Human detection
Smart analytics (important note)	IP camera alarms can only be utilized with Partizan Cloud platform, Partizan mobile application, and Partizan Cloud series video recorders.
Desktop apps	Setup Tool, Myers
Mobile app	Myers

Web browsers	Google Chrome, Mozilla Firefox, Edge
Web browser languages	English, Russian, Arabic, French, Polish, Romanian, Hungarian, Italian, Czech
Web browser usage (important note)	Web browser access requires Partizan ActiveX installation for device setup and live view. Available at www.apps.partizan.global
Mechanical specifications	
IP rating	IP67
Dimensions	100 x 72 x 71 mm
Weight	500 g
Housing material	Metal
Mount material	Metal
Power	
DC power source	12 V
DC consumption	1000 mA
PoE	PoE Class 0
Operating conditions	
Humidity range	20-95% RH (non-condensing)
Operating temperature	-40 - 60 °C
Storage temperature	-40 - 60 °C
Common	
Warranty	3 years