



Myers Outdoor WiFi Bullet IP camera equipped with a 1/2.7" CMOS sensor providing 2592×1944 resolution at 12 fps on the main stream with H.265 video compression. Features a 3.6mm spherical lens with M12 mount providing 65° horizontal and 39° vertical field of view. Includes both white LED and IR LED illumination with 20m range for day/night operation. Supports smart analytics including human detection, line crossing detection, and intrusion detection. Features built-in microphone and speaker for two-way audio, with TF card storage up to 128GB. IP66-rated metal housing operates from -40°C to 60°C, powered by 12V DC at 600mA consumption.

Product details	
Model	Outdoor
Version	WiFi Bullet
SKU	5933
Encoder	
Main stream	2592x1944@12 fps
Sub stream	640x360@12 fps
Video codec	H.265
Image sensor	
Sensor	1/2.7" CMOS
Pixel size	2.0x2.0 μm
Day/Night mode	Auto, Color, Black&White
Sensitivity	0.001 Lux
Dynamic range WDR	72 dB
S/N ratio	48 dB
Exposure modes	Auto, Manual
Exposure range	1/50 - 1/10000 s
Video functions	AES, AGC, BLC, OSD, Privacy mask
Lens	



Lens type	Spherical
Lens mount	M12
Iris	F1.4
Focal length	3.6 mm
Horizontal view	65°
Vertical view	39°
IR LED	
LED type	White LED, IR LED
Distance	≤20 m
Number of LEDs	4 pcs
Network	
Network interfaces	RJ-45 (10/100Base-T)
Network functions	DDNS, IP FILTER, Email, NTP, UPnP, RTP/RTSP, HTTP, HTTPS, TCP/IP
Default IP address	DHCP
HTTP(s) port	80
Control port	34567
RTSP port	554
RTSP URL	rtsp://IP:PORT/user=LOGIN&password=PASSWORD&channel=1&stream=0.sdp
Default credentials	
Default login	admin
Default password	admin
Software	
Smart analytics	Human detection, Line crossing detection, Intrusion detection
Smart analytics (important note)	IP camera alarms can only be utilized with Partizan Cloud platform, Partizan mobile application, and Partizan Cloud series video recorders.
Cloud abilities	Remote access, Cloud recording, PUSH notifications
Desktop apps	Myers, Myers Setup Tool



Mobile app	Partizan
Web browsers	Google Chrome, Mozilla Firefox, Edge
Web browser languages	English, Russian, Arabic, French, Polish, Romanian, Hungarian, Italian, Czech
Web browser usage (important note)	Web browser access requires Partizan ActiveX installation for device setup and live view. Available at www.apps.partizan.global
External interfaces	
Mic	Built-in microphone
Speaker	Built-in speaker
TF card support	≤128 Gb
Mechanical specifications	
IP rating	IP66
Dimensions	175 x 70 x 65 mm
Weight	650 g
Housing material	Metal
Mount material	Metal
Power	
DC power source	12 V
DC consumption	600 mA
DC power supply	Included
Operating conditions	
Humidity range	20-95% RH (non-condensing)
Operating temperature	-40 - 60 °C
Storage temperature	-40 - 60 °C
Common	
Warranty	3 years