



- Wi-Fi IP network video recorder
- Smart functions support
- 8-channel 5Mp record
- 1xSATA (max. 14Tb)
- ONVIF 2.4 protocol support
- Support mobile monitoring: iOS & Android

Your manual is here:

www.doc.myershome.eu/wifikit



Myers software:

<https://my.partizanccloud.com/get-our-mobile-app>



System		
Model		Myers 8CH WIFI KIT 4xBullet
Version		5MP
SKU		6015
Maximum connected cameras, pcs.		8
Operating system		Embedded Linux
Simultaneous multi-channel real-time		+
Playback		+
Network operation		+
USB backup		+
		<100
NVR		
Record		
Record, channels x resolution @ fps		8x5Mp@12, 8x3Mp@12, 8x2Mp@12
Record storage, HDD*/network		+/+
Video compression		H.264(HighProfile)/H.265
Space occupation for	Video	~80Gb(1080p), ~46Gb(960p), ~34Gb(720p), ~20Gb(D1),
	Audio	0.69Gb
*Please note, HDD is not included in the kit!		
Playback		
Playback archive records,		2x5Mp@12fps, 6x3Mp@12fps, 8x2Mp@12fps
Backup mode, network/USB		+/+
Preview screen		1/2/4/6/8/9
Record mode	Manual	+
	Alarm	+
	Motion Detection	+
	Schedule	+
Network		
Network Interface		1xRJ-45 (10/100Base-T)
Network functions		TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,
Languages supported		English, Russian, Arabic, French, Polish, Romanian, Hungarian, Italian, Czech
Default IP address		DHCP (Auto)
Default username		admin
Default password		admin
HTTP port		80
RTSP port		554
RTSP string		rtsp://192.168.1.10:554/user=admin&password=admin&channel=1&stream=0.sdp?
Control port		34567
Configuration software		Myers (Setup Tool), Myers Device Manager
Monitoring program		Myers
Mobile software (support)		Myers
Protocol integration		Myers SDK, ONVIF 2.4+
Interface		
Display quality		1920x1080; 1440x900; 1280x1024; 1280x720; 1024x768
Video	Inputs	-
	Outputs	1ch VGA, 1ch HDMI
Audio	Inputs	1ch TRS (3.5mm)
	Outputs	1ch TRS (3.5mm)
Alarm	Inputs	-
	Outputs	-
PTZ control, port/protocol support		Network
USB		2xUSB2.0
Internal SATA, pcs x max.Tb		1x14
External SATA, pcs x max.Tb		-
External eSATA, pcs x max.Tb		-
HDD operation mode		Single HDD
Smart Functions		
Channels / Functions		Human detection (Line Crossing, Perimeter Intrusion), Face
Dimensions		
Size, mm		255*43*215
Weight, g		750

- Wi-Fi IP camera
- 5Mp resolution
- IP67 rating
- IR + White LED + Smart Detection
- 24/7 Full Colour
- 3-Axis mounting
- ONVIF 2.4 protocol support

Common	
Power supply	DC12V, 2.0A
PoE/Class	-
Housing material, plastic/metal	-/+
Front material, plastic/metal	+/-
Operating temperature, °C	0 - +55
Warranty, years	3

IP Camera		
Model		Myers Wifi KIT Bullet
Version		5MP
Image Sensor		
Sensor		1/2.7" Full HD CMOS Sensor
Pixel Size, µm		2.8x2.8
Resolution, pixels@fps	Mainstream (max)*	PAL: 3840*2160@10fps NTSC: 3840*2160@10fps
	Substream (max)*	PAL: 800x448@25fps NTSC: 800x448@30fps
Day/Night mode	Auto	+
	Color	+
	Black&White	+
Sensitivity, Lux		0,01
Dynamic range WDR, dB		72
S/N ratio, dB		48
Video functions		AEC, AGS, AWB, ABF, BLC, OSD, PrivacyMasks
Smart functions		Human detected
Codec profile	H.264/H.265	Baseline / Main / High
Exposure mode, s	Auto	1/25-1/10000
	Manual	0.256-65.536
Bitrate Type, kb/s	Constant	1024-8192
	Variable	Worst/Worse/General/Good/Better/Best
*Attention! When you set the mainstream to the maximum fps, it may cause decreasing of fps of the substream		
Lens		
Focal length, mm		3,6
Iris, F		1,4
Angle of View, °	Horizontal	77
	Vertical	61
Lens Type	Aspherical	-
	Spherical	+
Lens mount		M12
Control, Manual/Auto		-
IR LED		
Distance, m		≤25
Number of LEDs, pcs.		2 double IR and White led
Beam Spread, °		60
Wavelength, nm		850
IR Cut Filter, Manual/Auto		-/+
Network		
Network Interface		RJ-45 (10/100Base-T)
Wireless LAN	Standard	802.11(b/g/n)
	Frequency, Ghz	2.4, 5db antenna
	Max. wireless	<100
Network functions		Partizan MAC protocol/DDNS/IPFilter/
Languages supported		English, Russian, Arabic, French, Polish, Romanian, Hungarian, Italian, Czech
Username		admin
Password		
HTTP port		80
ONVIF port		8899
RTSP port		554
RTSP string		rtsp://IPaddress:port/user=admin&password=&channel=1&stream=0.sdp?
Snapshot capture link		http://IPaddress/webcapture.jpg?command=snap&channel=1&user=admin&password=
Control port		34567
Configuration software		Myers (Setup Tool), Myers Device Manager
Monitoring program		Myers
Mobile software (support)		Myers
Protocol integration		Myers SDK, ONVIF 2.4+
Dimensions		
Size, mm	Total length	185
	Housing	60x70x110
	Bracket	70
Weight, g		350

Common		
Power Supply	DC12V, A	1
	PoE Class/W	-
Audio		-
Housing material, plastic/metal		-/+
Bracket material, plastic/metal		-/+
IP rating		67
IK rating		-
Operating temperature, °C		-40 - +60
Warranty, years		3

Inside the Kit:		
Wi-Fi NVR		1
Wi-Fi IP camera		4
Power supply		5
Mouse		1
Lan cable		1
Wi-Fi antenna		4
Mounting Kit		1