



- 4.0 Mp resolution
- High sensitivity
- Smart functions support
- IP66 rating
- IR LED
- ONVIF 2.4 protocol support
- 3-axis mounting
- Support mobile monitoring: iOS & Android
- Remote access to the device with Partizan MAC
- Ability to work with Partizan Cloud Storage

Your manual is here:

<http://manuals.partizan.global>



Partizan software:

<http://apps.partizan.global>



IP Camera		
Model	IPO-2SP SE	
Version	4.6 Cloud	
SKU	3107	
Image Sensor		
Sensor	1/2.8" FullHD CMOS	
Pixel Size, μm	2.9x2.9	
Resolution, pixels@fps	Mainstream (max)*	PAL: 4Mp@20, 3Mp@25, 2Mp@25
	Substream (max)*	PAL: 800x448@25
Day/Night mode	Auto	+
	Color	+
	Black&White	+
Sensitivity, Lux	0.01	
Dynamic range WDR, dB	72	
S/N ratio, dB	48	
Video functions	AES, AGC, AWB, BLC, OSD, Privacy masks	
Smart functions	Human detection	
Smart functions when using together with Cloud-series NVR	Human detection / Human Perimeter Intrusion Detection / Human Line Crossing Detection	
Codec profile	H.265/H.265X	Baseline / Main / High
Exposure mode, s	Auto	1/50-1/10000
	Manual	0.256-65.536
Bitrate Type, kb/s	Constant	1090-7271
	Variable	Worst/Worse/General/Good/Better/Best
*Attention! When you set the mainstream to the maximum fps, it may cause decreasing of fps of the substream		
Lens		
Focal length, mm	2.8	
Iris, F	1.4	
Angle of View, $^{\circ}$	Horizontal	89
	Vertical	58
Control, Manual/Auto	-	
IR LED		
Distance, m	≤ 30	
Number of LEDs, pcs.	30	
Beam Spread, $^{\circ}$	60	
Wavelength, nm	850	
IR Cut Filter, Manual/Auto	-/+	
Network		
Network Interface	RJ-45 (10/100Base-T)	
Network functions	Cloud/NiP/DDNS/IPFilter/E-mail/NTP/UPNP/RTSP	
Languages supported	English, Italian, Spanish, Russian, French, German, Poland, Romanian, Hungarian, Ukrainian, Hebrew, Arabic, Czech	
Default IP address	DHCP (Auto)	
Username	admin	
Password	admin	
HTTP port	80	
ONVIF port	8899	
RTSP port	554	
RTSP string	rtsp://IPaddress:port/user=admin&password=admin&channel=1&stream=0.sdp?	
Snapshot capture link	http://IPaddress/webcapture.jpg?command=snap&channel=1&user=admin&password=admin	
Control port	34567	
Configuration software	Partizan (Setup Tool), Partizan Device Manager	
Monitoring program	Partizan	
Mobile software (support)	Partizan	
Protocol integration	Partizan SDK, ONVIF 2.4+ (Profile S)	

Dimensions		
Size, mm	Total length	180
	Housing	Ø63x105
	Bracket	Ø55x75
Weight, g		360
Common		
Power Supply	DC12V, A	0.5
	PoE Class/W	0/6
Alarm	Inputs	-
	Outputs	-
Audio	Built-in microphone	-
	Inputs	-
	Outputs	-
Memory card		-
Housing material, plastic/metal		-/+
Bracket material, plastic/metal		-/+
IP rating		66
Operating temperature, °C		-40 - +60
Warranty, years		3