



The Partizan IPS-204X-IR 4K FADA SH is a CCTV camera featuring a 1/2.7" CMOS sensor that supports video resolutions up to 3840x2160 at 25 fps. This device includes both NTSC and PAL mainstream and substream outputs, with various resolution options. It operates in a temperature range from -40°C to +60°C and is housed in IP66-rated plastic for weather resistance. The camera provides motorized zoom and features infrared illumination with a distance of 30 meters and a beam spread of 80 degrees, enabling enhanced night vision capabilities.

3-Axis mounting
High sensitivity with starvis technology
IP 66 Rating
IR LED
Partizan mobile app
Record to Partizan Cloud Storage
SD card support
Smart functions support

Product details	
Model	IPS-204X-IR 4K FADA SH
SKU	3533
Image sensor	
PAL Mainstream	3840x2160@25 fps, 3072x1728@25 fps, 2592x1944@25 fps, 2592x1520@25 fps, 2304x1296@25 fps, 1920x1080@25 fps, 1280x960@25 fps, 1280x720@25 fps
PAL Substream	1280x720@25 fps, 640x480@25 fps, 320x240@25 fps
Bitrate type (manual)	256 kb/s - 16384 kb/s
Bitrate type (variable)	Lowest, Lower, Low, Medium, Higher, Highest
Codec profile 264	Baseline, Main, Hight
Codec profile 265	Baseline, Main, Hight
Day/Night mode	Auto, Color, Black&White
Dynamic range WDR	120 dB
Exposure modes	Auto, Manual
Exposure range	0.256 - 65236 s
Pixel size	2.0x2.0 μm
S/N ratio	50 dB

Sensitivity	0.009Lux
Sensor	1/27" CMOS
Funciones de video	BLC, HLC, WDR, AGC, Obturador lento, Máscaras de privacidad
<b>Lens</b>	
Control	Motorized
Focal length	2.8 - 12 mm
Horizontal view	31.4 - 113 °
Iris	1.6F
Lens type	Spherical
Vertical view	17.6 - 58.4 °
Zoom	Motorized
<b>IR LED</b>	
Beam spread	80°
Distance	30m
IR cut filter	Auto
Number of LEDs	4pcs
Wavelength	850nm
<b>Network</b>	
Control port	9988
Default IP address	DHCP
HTTP(s) port	80
Network functions	DHCP, DNS, DDNS, RTP/RTSP, PPPoE, SMTP, NTP, UPnP, SNMP
Network interfaces	RJ-45 (10/100Base-T)
ONVIF port	80
ONVIF support	ONVIF 2.6
RTSP port	554
RTSP URL	rtsp://IP:554/rtsp/streaming?channel=1&subtype=0&onvif_metadata=true
<b>Smart camera features</b>	

Funciones inteligentes	Detección de rostros, Detección de peatones, Detección de vehículos, Detección de intrusión perimetral, Detección de cruce de línea, Conteo cruzado, Detección de objetos en posición fija, Mapa de calor, Detección de densidad de multitudes, Detección de longitud de cola, Detección de matrículas, Detección de sonidos raros, Detección de entrada de región, Detección de salida de región, Reconocimiento facial (Requiere NVR), Reconocimiento de matrículas (Requiere NVR)
<b>Default credentials</b>	
Default login	admin
Default password	admin
<b>Software</b>	
Cloud abilities	Remote access, Cloud recording, PUSH notifications
Desktop apps	Setup Tool, Partizan
Mobile app	Partizan
Lenguajes de navegador web	Inglés, finlandés, Ruso, Checo, Holland, Árabe, Ucraniano, Turco, Español, Portugués, Italiano, Alemán, Francés
Navegadores web	Internet Explorer
<b>External interfaces</b>	
Mic	Built-in microphone
Speaker	Built-in speaker
TF Card	≤256 Gb
<b>Power</b>	
DC consumption	1500 mA
DC power source	12V
DC power supply	Included
PoE	PoE Class 0
<b>Physical specification</b>	
Dimensions	182x122x238 mm
Housing material	Plastic
IP rating	IP 66
Mount material	Plastic

Operational temperature	-40 °C ... +60 °C
Weight	920g
<b>Common</b>	
Waranty	3Years